

S&V Test results	AVR-X7200WA	AV8802	AV8801/MM8077	MM8003
THD+N	0.006%	0.008%	0.017%	
CT	-93.91/-94.53 dB	-92.21/-93.16 dB	-81.35/-83.6 dB	
SNR	-108.20 dBrA	-130.38 dBrA	-124.15 dBrA	
FR (Pure Direct)	-0.04 dB at 10 Hz -0.00 at 20 Hz -0.06 dB at 20 kHz -3.51 dB at 50 kHz	-0.14 dB at 10 Hz -0.04 at 20 Hz -0.01 dB at 20 kHz -0.05 dB at 50 kHz	-0.19 dB at 10 Hz -0.05 at 20 Hz -0.01 dB at 20 kHz -0.04 dB at 50 kHz	
FR (with SP)	-0.81 dB at 10 Hz -0.23 dB at 20 Hz -0.42 dB at 20 kHz -20.36 dB at 50 kHz	-0.84 dB at 10 Hz -0.25 dB at 20 Hz -3.29 dB at 20 kHz -55.14 dB at 50 kHz	-1.23 dB at 10 Hz -0.39 dB at 20 Hz -0.21 dB at 20 kHz -15.78dB at 50 kHz	
LFE	+0.01 dB at 20 Hz -3 dB at 118 Hz -6 dB at 121 Hz	Same Same Same	-0.00 dB at 20 Hz -3 dB at 118 Hz -6 dB at 121 Hz	
2 Ch into 8 ohm	146.6 W 0.1% THD 185.8 W 1 % THD		128.4 W 0.1% THD 150.3 W 1 % THD	174.8 W 0.1% THD 192.5 W 1 % THD
2 Ch into 4 ohm	234.7 W 0.1% THD 265.5 W 1% THD		220.2 W 0.1% THD 241.8 W 1% THD	248 W 0.1% THD 289.1 W 1% THD
5 Ch into 8 ohm	122.3 W 0.1% 138 W 1%		113.9 W 0.1% 125.4 W 1%	127.1 W 0.1% 150.1 W 1%
7 Ch into 8 ohm	113.7 W 0.1% 124.0 W 1%		108.9 W 0.1% 116.8 W 1%	
8 ch into 8 ohm				109.7 W 0.1% 122.3 W 1%
CT RCA			-70.84 dB/-70.72 dB	
CT XLR			-71.31 dB/-71.46 dB	
SNR RCA			-114.83 dBrA	
SNR XLR			-104.31 dBrA	