

Bowers & Wilkins (B&W) CM Centre 2 S2 specs



GENERAL INFO	
Recommended usage:	Center
Type:	Bookshelf
Enclosure type:	Vented (bass reflex)
Port (bass reflex) location:	Front
Frequency range:	70Hz (measured at -3dB) - 28kHz
Recommended power:	30W - 120W
Sensitivity:	87dB at 2.83V/1m
Nominal impedance:	8 ohms
Minimal impedance:	3 ohms
Number of drivers:	3
Number of frequency bands:	2-way
Crossover frequencies:	4000Hz
DRIVERS INFORMATION	
Drivers include:	Woofer / Midbass, Tweeter
Woofer/Midbass:	2 x 5 in
Woofer/Midbass's cone material:	Kevlar / Glass Fiber / Carbon Fiber
Tweeter:	1 x 25 mm
OTHER FEATURES	
Built-in amplifier:	No
Built-in digital decoder (DAC):	No

BODY	
Enclosure materials:	MDF
Dimensions (WxHxD):	18.9 in x 6.56 in x 10.24 in
Weight:	25.35 lb
Available color options:	Black
US AVAILABILITY	
Market status:	Available
EUROPEAN AVAILABILITY	
Market status:	Available
LINKS	
Official page:	link
in English:	