

VI. SPECIFICATIONS

	Alpha Intro LR Compact Monitor	Alpha Intro CLR Center/Monitor	Alpha S Surround
FREQUENCY RANGE Response On Axis @ 0° ± 3dB Off Axis @ 30° ± 3dB LF Cutoff -10dB	(Anechoic Chamber) 100-21,000Hz 100-10,000Hz 90Hz	 90-21,000Hz 100-10,000Hz 80Hz	 85-21,000Hz 85-10,000Hz 75Hz
SENSITIVITY Anechoic Chamber Typical Listening Room	(1W (2.83V) @ 1m, IEC-filtered Pink Noise, C-weighted) 85dB 87dB	 86dB 88dB	 86dB 88dB
IMPEDANCE Nominal Minimum	6 Ohms 4 Ohms	8 Ohms 6 Ohms	8 Ohms 6 Ohms
INPUT POWER Recommended Program	(RMS, Clipping < 10% Time) 15-80 Watts 60 Watts	15-80 Watts 60 Watts	15-80 Watts 60 Watts
ACOUSTIC DESIGN Tweeter (Nominal) Woofer (Nominal) Crossover Internal Volume Design Type	¾ (19mm) Aluminum Dome with Ferrofluid 3½" (90mm) Polypropylene Cone Rubber Surround 3,000Hz, B3 0.07 cu ft (2.0 liter) Acoustic Suspension Sealed Video Shielded	¾ (19mm) Aluminum Dome with Ferrofluid 2 x 3½" (90mm) Polypropylene Cone Rubber Surround 3,000Hz, B3 0.10 cu ft (2.8 liter) Acoustic Suspension Sealed Video Shielded	2 x ¾ (19mm) Aluminum Dome with Ferrofluid 2 x 3½" (90mm) Polypropylene Cone Rubber Surround 3,000Hz, B3 0.10 cu ft (2.8 liter) Acoustic Suspension Bipole Video Shielded
SIZE (W x H x D)	4¼" x 6¼" x 6¼" 108mm x 171mm x 159mm	9¾" x 4¼" x 6¼" 248mm x 108mm x 159mm	9¼" x 6¼" x 4¾" 235mm x 171mm x 121mm
WEIGHT Net Shipping	3.3lb (1.5kg)/each 7.6lb (3.5kg)/pair	4.8lb (2.2kg)/each 5.6lb (2.6kg)/each	4.9lb (2.2kg)/each 10.8lb (4.9kg)/pair
FINISH	Black or White Textured	Black or White Textured	Black or White Textured
FEATURES	5-way Gold-plated Binding Posts, Perforated Aluminum Grille, Structural Plastic Front Baffle, ½" (13mm) MDF Sleeve, Structural Plastic Rear Baffle with Keyhole slot & ¼-20 Brass Insert, Wall or Bottom Rubber Bumpers	5-way Gold-plated Binding Posts, Perforated Aluminum Grille, Structural Plastic Front Baffle, ½" (13mm) MDF Sleeve, Structural Plastic Rear Baffle with Horizontal/Vertical Keyhole slots & ¼-20 Brass Insert, Wall or Bottom Rubber Bumpers	5-way Gold-plated Binding Posts, Perforated Aluminum Grille, Structural Plastic Front Baffle, ½" (13mm) MDF Sleeve, Keyhole Wall Mounting Plate Rubber Bumpers
STANDS	Optional Alpha Intro Stands	Optional Alpha Intro Stands	

All specifications are subject to change without notice. PSB® is a trademark of Lenbrook Corp., used under license by PSB Speakers®, a division of Lenbrook Industries Limited. © 2000 PSB Speakers. All rights reserved.